




PCT / IB 03 / 03580  
07.08.03



#2

INVESTOR IN PEOPLE



The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.


In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed *He Behen*

Dated 5 June 2003



BEST AVAILABLE COPY

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)



The  
Patent  
Office  
□□□□

28AUG02 E743974-2 0028 9  
P01/7700 0.00-0219910.7

1/77

**Request for grant of a patent**  
(See notes on the back of this form. You can  
also get an explanatory leaflet from the Patent  
Office to help you fill in this form)

The Patent Office  
Cardiff Road  
Newport  
Gwent NP10 8QQ

Your reference PHGB020140

Patent application number 28 AUG 2002 0219910.7  
(The Patent Office will fill in this part)

Full name, address and postcode of the or of  
each applicant (underline all surnames)  
07419294001  
Patents ADP Number (if you know it)  
If the applicant is a corporate body, give the  
country/state of its incorporation THE NETHERLANDS

KONINKLIJKE PHILIPS ELECTRONICS N.V.  
GROENEWOUDSEWEG 1  
5621 BA EINDHOVEN  
THE NETHERLANDS

1. Title of the invention WEDGE-BONDING OF WIRES IN ELECTRONIC DEVICE MANUFACTURE

5. Name of your agent (if you have one)  
"Address for service" in the United Kingdom  
to which all correspondence should be sent  
(including the postcode)  
Patents ADP number (if you know it) 07489050002

BRIAN T STEVENS  
Philips Intellectual Property and Standards  
Cross Oak Lane  
Redhill  
Surrey RH1 5HA

6. If you are declaring priority from one or more  
earlier patent applications, give the country  
and the date of filing of the or of each of these  
earlier applications and (if you know it) the or  
each application number

Country Priority Application number Date of filing  
(if you know it) (day/month/year)

7. If this application is divided or otherwise  
derived from an earlier UK application, give  
the number and the filing date of the earlier  
application

Number of earlier application Date of filing  
(day/month/year)

8. Is a statement of inventorship and of right to  
grant of a patent required in support of this  
request? (Answer "Yes" if:  
a) any applicant named in part 3 is not an inventor, or  
b) there is an inventor who is not named as an  
applicant, or  
c) any named applicant is a corporate body.  
See note (d)) YES

Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document.

Continuation sheets of this form

Description	
Claims(s)	5
Abstract	2
Drawings	1
	2 only 16

3. If you are also filing any of the following, state how many against each item:

Priority Documents

- Translations of priority documents
- Statement of inventorship and right to grant of a patent (*Patents Form 7/77*).
- Request for preliminary examination and search (*Patents Form 9/77*)
- Request for substantive examination (*Patents Form 10/77*)
- Any other documents  
(Please specify)

1. I/We request the grant of a patent on the basis of this application.

Signature 101.82 Date 27-08-2002

2. Name and daytime telephone number of person to contact in the United Kingdom 01293 815294 (Brian T Stevens)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been evoked.

Notes

- 1) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- 2) Write your answers in capital letters using black ink or you may type them.
- 3) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- 4) If you have answered "Yes" Patents Form 7/77 will need to be filed.
- 5) Once you have filled in the form you must remember to sign and date it.
- 6) For details of the fee and ways to pay please contact the Patent Office.

## DESCRIPTION

**WEDGE-BONDING OF WIRES IN ELECTRONIC DEVICE MANUFACTURE**

5           This invention relates to the wedge-bonding of wires in the manufacture of electronic devices. In particular, it relates to wedge-bonding methods, machines and tools, and also to electronic devices that include connections in the form of wires which are wedge-bonded using such methods or machines or tools.

10           The wedge-bonding of wires is a well-established technology that has been used for many decades to provide connections in electronic devices. By way of example, the following is a selection of recent United States patents on wedge bonding: US-A-6,354,479, US-A-6,135,341, US-A-5,958,270, US-A-5,950,903, US-A-5,945,065, US-A-5,906,706, US-A-5,836,071, 15 US-A-5,702,049, US-A-5,495,976, US-A-5,452,838, US-A-5,445,306, US-A-5,364,004, US-A-5,148,959, US-A-5,018,658, and US-A-5,007,576. The whole contents of these US patents are hereby incorporated herein as reference material. The bonding tool (typically of tungsten carbide) generally comprises a shank having the wedge-bonding tip at one end.

20           There is always a desire for cost reduction. One of the many items that involves an on-going cost is the need to periodically replace the bond tool when its bonding tip is becoming worn through use.

25           It is an aim of the present invention to reduce the cost of replacing the bond tool.

          According to one aspect of the invention, there is provided a reversible bonding tool having a wedge-bonding tip at opposite ends of the tool. Thus, the present invention provides a dual-tip reversible tool, that increases the use time before replacement of the tool is required. Thus, a saving can be achieved 30 in tool material.

According to another aspect of the invention, there are provided wire-bonding machines having such a reversible bonding tool in accordance with the present invention.

According to further aspect of the invention, there are provided wedge-bonding methods, wherein:

- a reversible bonding tool in accordance with the present invention is used,
- and, after using the tip at one end for bonding wires, the tool is reversed to use the wedge-bonding tip at the opposite end for bonding further wires.

According to yet another aspect of the invention, there are provided electronic devices, for example an integrated circuit or a power semiconductor device, that include connections in the form of wires which are wedge-bonded using such a method or machine or tool in accordance with the present invention.

Various advantageous features and feature-combinations in accordance with the present invention are set out in the appended Claims. These and others are illustrated in embodiments of the invention that are now described, by way of example, with reference to the accompanying diagrammatic drawings, in which:

Figures 1A and 1B are a schematic side-view of part of an ultrasonic wedge-bonding machine in an embodiment of the present invention, during use at successive times in the manufacture of electronic devices;

Figure 2A is a downward-looking perspective view of the reversible bonding tool of Figure 1, particularly of its working ends, and showing a bonding tip at its upper end in accordance with the invention; and

Figure 2B is an upward-looking perspective view of the lower working end of the bonding tool of Figure 2, showing the bonding tip at this lower end.

It should be noted that all the Figures are diagrammatic. Relative dimensions and proportions of parts of these Figures have been shown exaggerated or reduced in size, for the sake of clarity and convenience in the

drawings. The same reference signs are generally used to refer to corresponding or similar features in modified and different embodiments.

Figures 1A and 1B illustrate a wire-bonding stage in the manufacture of electronic devices 20, 20', for example discrete semiconductor power devices or semiconductor integrated circuits (ICs). A reversible dual-tip bonding tool 10 is used having a bonding tip (also termed "wedge") 1, 2 at each of the opposite ends 11, 12 of the tool, see Figure 2A and 2B.

After extensive use of the wedge-bonding tip 1 at one end 11 for bonding wires 21 (as illustrated in Figure 1A), the tip 1 is worn somewhat. Instead of needing to replace the bond tool as in the prior art, the tool 10 in accordance with the present invention is then reversed to use the wedge-bonding tip 2 at the opposite end 12 for bonding further wires 21' (as illustrated in Figure 1B). Thus, a cost saving is achieved with regard to tool material.

Apart from using the reversible tool 10 in accordance with the present invention, the wedge-bonding process and the wire-bonding machine may be of known forms and so will not be described in detail.

Thus, Figures 1A and 1B illustrate the work area of the machine, where the device 20, 20' is placed on a work mount 32. Wire 21, 21' is fed continually into this work area from a spool (not shown). The wire 21, 21' is fed to a bond pad 23, 23' of the device 20, 20', and it is pressed against the bond pad 23, 23' by the lower working end (11 in Figure 1A; 12 in Figure 1B) of the tool 10. The wire 21, 21' may comprise aluminium (typically an Al alloy) for both discrete power devices and for ICs, and the bond pad 23, 23' may also comprise aluminium. In some devices, it may be preferred to use gold wire 21, 21'. The wire 21, 21' forms connections between, for example, the bond pad 23, 23' and terminal leads of the device package (not shown).

While being pressed against the bond pad 23, 23' the wire 21, 21' is bonded to the pad 23, 23' by turning on an ultrasonic source to a transducer 30 that applies ultrasonic energy to the wire 21, 21' on the pad 23, 23' via the respective bonding tip 1 or 2 of the tool 10. Figures 1A and 1B schematically

show the tool 10 mounted in a horn of the transducer 30. This horn is coupled to the ultrasonic source (not shown) of the ultrasonic energy.

In the embodiment illustrated in Figures 1A and 1B, the bond tool 10 comprises a shank having tapered work ends 11 and 12 at the opposite ends of the shank. Narrow bonding tips 1 and 2 (which engage with the wire 21, 21' to be bonded) are present at these work ends, specific embodiments being shown in Figures 2A and 2B. There are a variety of known geometries and structures that may be adopted for the work end and wedge tip. Figures 1A, 1B, 2A and 2B illustrate a very simple grooved structure in which the wedge-bonding tips 1, 2 and the opposite working ends 11, 12 of the tool 10 are integral with the shank. In this case, the entire bonding tool 10 (including its shank) may be of tungsten carbide.

Figures 1A and 1B do not show any detail of the wire-bonding machine in respect of the mounting of the tool 10 in the transducer horn 30. This mount 31 couples the tool 10 ultrasonically to the transducer in known manner. However, the mount 31 is of such a form as also to allow the tool 10 to be reversed, thereby permitting wire bonding using either the wedge-bonding tip 1 at one end 11 (Figure 1A) or the wedge-bonding tip 2 at the opposite end 12 (Figure 1B). This reversible mount aspect is most readily achievable when the mount 31 engages the tool 10 at a position on the shank between its opposite ends 11, 12, as illustrated in Figures 1A and 1B.

The drawings have shown only a very simple basic form for the tool and a schematic representation of the machine and of the bonding process. It will be apparent to persons skilled in the art that this basic form can be extended, embellished and modified with the type of features that are commonly used or sometimes used in the art. Thus, for example, Figure 1 does not show how the wire 21, 21' may be guided and fed to the device bond pad 23, 23'. A guide that is external to the bond tool 10 may be used, and/or a guide hole may be present in the bond tool 10. Separate guide holes (providing a through passage for the wire 21, 21') may extend obliquely through each end 11, 12 of the tool 10, or there may be a single guide hole (in the form of a capillary bore) that extends through the length of the tool 10.

In the embodiment described above, the whole bond tool 10 composed of tungsten carbide. However, other embodiments may be used with other materials, for example, hardened steel and titanium carbide, and different materials may be used for different parts of the tool 10 (the shank, the work-ends 11 and 12, and the bonding tips 1 and 2 themselves).

From reading the present disclosure, many other variations and modifications will be apparent to persons skilled in the art. Such variations and modifications may involve equivalent and other features which are already known in the design, manufacture and use of wedge-bonding tools and machines and of electronic devices having wedge-bonded wires, and which may be used instead of or in addition to features already described herein. Examples of such features are to be found in the US patents cited herein previously as reference material.

Although Claims have been formulated in this Application to particular combinations of features, it should be understood that the scope of the disclosure of the present invention also includes any novel feature or any novel combination of features disclosed herein either explicitly or implicitly or any generalisation thereof, whether or not it relates to the same invention as presently claimed in any Claim and whether or not it mitigates any or all of the same technical problems as does the present invention.

The Applicants hereby give notice that new Claims may be formulated to such features and/or combinations of such features during the prosecution of the present Application or of any further Application derived therefrom.



## CLAIMS:

---

1. A method of wedge-bonding wires in the manufacture of electronic devices, wherein:-----

- 5       • a reversible bonding tool is used having a wedge-bonding tip at opposite ends of the tool,
- and, after using the wedge-bonding tip at one end for bonding wires, the tool is reversed to use the wedge-bonding tip at the opposite end for bonding further wires.

10

2. A method according to Claim 1, wherein the bonding tool comprises a shank of tungsten carbide having the wedge-bonding tips at opposite ends of the shank.

15

3. A method according to Claim 1 or Claim 2, wherein the wires comprise aluminium or gold and are ultra-sonically bonded using a transducer coupled to the tool.

20

4. A wire-bonding machine for ultrasonic wedge-bonding of wires in the manufacture of electronic devices, wherein the machine includes a reversible bonding tool having a wedge-bonding tip at opposite ends of the tool, and a mount for coupling the tool to an ultrasonic transducer, the mount allowing the tool to be reversed so as to permit wire bonding using either the wedge-bonding tip at one end or the wedge-bonding tip at the opposite end.

25

5. A wire-bonding machine according to Claim 4, wherein the bonding tool comprises a shank having the wedge-bonding tips at opposite ends of the shank, and wherein the mount engages the tool at a position on the shank between its opposite ends.

30

---

6. A reversible bonding tool for use in a method according to any one of Claims 1 to 3 or in a machine according to Claim 4 or Claim 5, wherein the tool comprises a shank having a wedge-bonding tip at opposite ends of the shank.

---

5           7. A machine according to Claim 4 or Claim 5 or a tool according to Claim 6, wherein at least the wedge-bonding tips at opposite ends are of tungsten carbide.

10           8. An electronic device, for example an integrated circuit or a power semiconductor device, that includes connections in the form of wires which are wedge-bonded using a method or machine or tool according to any one of the preceding Claims.

## ABSTRACT

---


**WEDGE-BONDING OF WIRES IN ELECTRONIC DEVICE MANUFACTURE**

---



5           In the manufacture of electronic devices (22, 22'), e.g. discrete semiconductor power devices or ICs, a reversible bonding tool (10) is used having a bonding tip or wedge (1, 2) at each of its opposite ends (11, 12). After extensive use of the wedge-tip (1) at one end (11) for bonding wires (21), the tip (1) is worn somewhat. Instead of needing to replace the bond tool as in the prior art, the tool (10) in accordance with the invention is then reversed to use the  
10           wedge-tip (2) at the opposite end (12) for bonding further wires (20'). Thus, a cost saving is achieved with regard to tool material.

---

15           [Figures 2A & 2B]




1/2



PNGB020140

2/2



PHGB020140

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**